


NOTES: SIDE BARRIER MARKERS SHALL BE YELLOW IN COLOR WHEN PLACED ON MEDIAN-SIDE BARRIER (SEPARATING OPPOSING TRAFFIC).

SIDE BARRIER MARKERS SHALL BE WHITE IN COLOR WHEN PLACED ON SHOULDER-SIDE BARRIER (OR BARRIER SEPARATING SAME DIRECTION TRAFFIC).

THE 48 FOOT SPACINGS BETWEEN MARKERS SHALL BE MAINTAINED ON CURVES/TURNS.

INSTALL SIDE MARKERS IN CONFORMANCE WITH MANUFACTURERS DIRECTIONS.

THE BOTTOM OF THE TOP MARKER SHALL BE AT THE SAME ELEVATION AS THE TOP OF THE BARRIER. NO ATTACHMENT METHOD MAY BLOCK ANY PART OF THE REFLECTIVE AREA OF THE MARKER. BACKING FOR TOP MARKERS SHALL BE SHEET ALUMINUM, MEETING MATERIAL THICKNESS PER TEMPORARY TRAFFIC SIGNS SPECIFICATIONS OR ANY OTHER MATERIAL APPROVED BY OOTS.



REVISED

REVISED

REVISED

REVISED

REVISED

StateHighway

Maryland Department of Transportation STATE HIGHWAY ADMINISTRATION

STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES

BARRIER DELINEATION
BARRIER 4 FEET OR CLOSER TO EDGE LINE

STANDARD NO.

MD 104.01-25